HaiNan SynYune EV Technology Co.,Ltd battery-generator.com

30KW OCPP EV Charging Pile Dc Fast Charging Stations

Basic Information

Place of Origin: China
Brand Name: N/A
Certification: TUV CE
Model Number: EVP30
Minimum Order Quantity: 1

• Price: USD5000~25000/unit

Packaging Details: 1units/pckDelivery Time: 15days

Payment Terms:
 L/C, T/T, Western Union

• Supply Ability: 1000pcs/month



Product Specification

Model Nunber: EVP30

• Type: DC Charger, FAST Charger

Input Current: 45A
Maxium Output Power: 30KW
Input Voltage: 400V+10%
Output Voltage: 200-1000Vdc

Maxium Output Current: 75AMax Effeciency: 94%

• Dimension: 707*560*217mm

• Weight: 35.3kg

• Highlight: 30KW EV Charging Pile, OCPP EV Charging Pile

, 30KW dc fast charging stations $\,$



Product Description

High Quality 30KW EV Car Charger, Electric Car Charger applied for Charging Stations

Product Parameters:

Product Parameters:				
Techanical Ratings				
AC Input				
Connection type	U/V/W+N+PE			
Input voltage	400V±10%			
Input frequency	50Hz/60Hz±10%			
Rated power	30kW			
Max input current	45A			
Power factor	≥0.98, Maximum value			
THDi	<5%, Best case			
Max. efficiency	>94%			
DC Output	•			
Charging interface	Port A: CCS2 Port B: CCS2, IEC 62196-3, DIN70121			
Communication with EV	DIN 70121, ISO 15118			
Output voltage range	200-1000Vdc			
DC Output - When both gu	ins are used for charging at the same time			
Maximum output current	75A, each gun			
Rated output voltage1	400Vdc			
DC output — When only s	ingle gun is used			
Maximum output current	750A			
Maximum output power*	30kW			
HMI				
Touch screen	8-inch touch screen			
RFID2	IEC/ISO14443A/B, Mifare/Felica optional			
Payment terminal	Nayax VPOS touch			
Network	4G modem, Ethernet port *1			
Protocol for backend3	OCPP 1.6J			
Ambient Conditions				
Operating temp, range	-10°C~+50°C			
Operating humidity	5-95%			
Operating altitude	≤2000m			
Mechanical Data				
Dimension (W*D*nf	707*560*217mm			
Degree of protection	IP54			
Cooling method	Force air cooling			
Charging cable length	5.0m			
Noise level	≤75dB			
Weight	35.3kg			
Standard and Compliance	·			
Standard	IEC 61851-1, IEC 61851-23, IEC 61851-24, IEC 62619-3			
	IEC 61851-21-2, IEC 61800-2, IEC 61800-4			
Certification mark	TUV CE			

Products HD pictures:





P	ro	dυ	ct	Feasur	es:

DC Chargers we have:

Our R&D AND TECH TEAM:

Our Research Labs:

Our Testing:

Reference Projects:

Contact Form:



HaiNan SynYune EV Technology Co.,Ltd





SYJackie@163.com



a battery-generator.com

No. 4 Jipu Road, Xinyingwan District, Yangpu EDZ, Hainan Province